

PATENT

Attorney Docket No. 33816/US/RBC/VEJ
Attorney Matter No. 463678-00228
Application No. 10/726,220

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

in re application of:

Gerry MAVIN

Application No. 10/726,220

Filed: December 1, 2003

For: **METHOD AND APPARATUS FOR
APPLYING A THREADED CAP TO
A THREADED NECK OF A
CONTAINER**

Art Unit: 3721

Examiner: *To be assigned*

Docket No.: 33816/US/RBC/VEJ

Certificate of Mail (37 C.F.R. § 1.8(a))

I hereby certify that this paper (along with any referred to as being attached or enclosed) is being deposited with the United States Postal service on the date shown below with sufficient postage as first class mail in an envelope addressed to Mail Stop MISSING PARTS, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on 6-29-04

Patricia A. Diehl
Patricia A. Diehl

Mail Stop MISSING PARTS
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

TRANSMITTAL OF CERTIFIED COPY

Sir:

Please find enclosed herewith the certified copy of the foreign application from which priority is claimed for the above-captioned application:

Country:	UNITED KINGDOM
Application Number:	0228062.6
Filing Date:	2 December 2002

Respectfully submitted,

DORSEY & WHITNEY LLP

Date:

6/29/2004

By:

Victor E. Johnson

Victor E. Johnson, Reg. No. 41,546
/for/ Robert B. Chickering, Reg. No. 24,286

DORSEY & WHITNEY LLP
Four Embarcadero Center, Suite 3400
San Francisco, CA 94111-4187
Telephone: (415) 781-1989 Facsimile: (415) 398-3249

(1146373)

THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE


The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




Signed *Stephen Hordley*
Dated 9 December 2003

THIS PAGE BLANK (USPTO)

Patents Act 1977
(Rule 16)

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Concept House
Cardiff Road
Newport
South Wales NP10 8QQ

1. Your reference NAM/P61786/000

2. Patent application number
(The Patent Office will fill in this part)

0228062.6

- 2 DEC 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

PORTOLA PACKAGING LIMITED
3 CARRIAGE DRIVE
WHITE ROSE WAY
DONCASTER
SOUTH YORKSHIRE DN4 5NT
UNITED KINGDOM

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

UNITED KINGDOM

7154 271002

4. Title of the invention

METHOD AND APPARATUS FOR APPLYING A THREADED CAP TO A THREADED NECK OF A CONTAINER

5. Name of your agent (if you have one)

BOULT WADE TENNANT

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

VERULAM GARDENS
70 GRAY'S INN ROAD
LONDON WC1X 8BT

Patents ADP number (if you know it)

42001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day/month/year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request?

Yes

(Answer 'Yes' if:

a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant,

or

c) any named applicant is a corporate body.
See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form 0

Description 14

Claim(s) 6

Abstract 0

Drawing(s) 4

10. If you are also filing any of the following, state how many against each item.

Priority documents 0

Translations of priority documents 0

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 0

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77) 0

Any other documents 0
(Please specify)

11

I/We request the grant of a patent on the basis of this application.

Signature

Date

2 December 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

McLEISH; Nicholas Alistair Maxwell
020 7430 7500

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 01645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

METHOD AND APPARATUS FOR APPLYING A THREADED CAP TO A
THREADED NECK OF A CONTAINER

5 The present invention relates to a method and apparatus for applying a threaded cap to a threaded neck of a container.

The use of a threaded cap to close a container, where the container has a correspondingly threaded neck is well known. During packaging, after the
10 container has been filled, it is necessary to apply the cap to the neck of the container to seal the contents of the container and prevent leakage. Typically this is a two stage process.

Initially the cap is placed on the neck of the
15 container without substantial engagement of the threads. There are two commonly used methods of placing the cap on the container neck. In the first method, known as the "pick and place" method, a cap is collected by a capping head. The capping head
20 suspends the cap in a substantially horizontal plane and the cap is either lowered onto the neck of the container or else the container is raised up to meet the cap.

The second method is known as the "pick-off"
25 method. In this method, rather than the cap being suspended in a capping head and placed on the container neck, the caps are suspended above where the containers are transported, such that each cap is inclined with respect to the direction of motion of a
30 respective container. The incline of the cap is such that the container neck contacts the inside of the cap and removes the cap from the suspension point. The cap is thereby placed on the neck without substantial engagement of the threads. Once the suspended cap has
35 been removed from the suspension point another cap takes its place and the process is repeated with the

next container.

Once the cap has been placed on the neck of the container there are then two common ways of applying the cap onto the neck of the container such that the threads are in substantial engagement. The first method of application is by means of an axially downward force which causes the threads of the cap to slide over those of the container and then interengage.

A second method of applying the cap to the container neck is by rotating the cap relative to the neck of the container. This rotation takes place in the direction of rotation of the threads and is designed so that a predetermined torque is achieved between the cap and the container with the result that the threads are in substantial engagement.

A common problem with the use of the previously described methods is that if the cap is not placed on the neck so that the threads of the cap are in alignment with those of the neck, the subsequent application of the cap can result in cross-threading.

In addition, since the neck and cap are commonly made of different materials, with different hardnesses, if the threads are initially cross-threaded, the subsequent forced application of the cap to the neck by either method can result in the threads becoming damaged. This in turn may lead to subsequent problems with leakage encountered by retailers, distributors and consumers alike. Also, if the threads are damaged, there may be a problem with leakage even if the cap is removed and subsequently applied correctly.

It is also known that when the threads of the cap and neck are cross-threaded the removal of the cap may be significantly more difficult than if the threads are in alignment. This can cause problems for users with weakened capability such as the elderly or sick.

It is therefore desired to provide an apparatus and method of minimising the risk of cross-threading during the application of a threaded cap onto a threaded neck of a container.

5

STATEMENT OF THE INVENTION

According to a first aspect of the present invention, there is provided a method of applying a threaded cap to a threaded neck of a container, the method comprising the steps of: placing the cap on the neck of the container; rotating the cap relative to the neck in an opening direction whilst supporting the cap with respect to the neck; and applying the cap to the neck so as to achieve substantial thread engagement.

This is advantageous because if the cap is placed on the neck of the container with the threads of the cap and neck in misalignment, the rotation of the cap in the opening direction will correct this misalignment. This means that the threads will settle into correct alignment prior to the application of the cap onto the neck of the container. This has the result that the problem of cross-threading is alleviated, thereby reducing the risk of leakage. In addition, the problem of thread damage is also addressed.

Advantageously, the cap may be rotated relative to the neck in an opening direction through an angle of at least 360°.

Preferably, the cap is rotated relative to the neck in an opening direction through an angle of between 36° and 720°.

Advantageously, the cap may be applied to the neck by means of an axial force which causes the threads on the cap and the threads on the neck to move

)
past each other and then interengage. Alternatively, the cap may be applied to the neck by rotation of the cap relative to the neck in a closing direction.

5 In one embodiment of the present invention the cap may be drivingly rotated with respect to the neck by rotational drive means in both the opening and closing directions. Alternatively the cap may be drivingly rotated by rotational drive means in the closing direction and rotated against the rotational
10 drive means in the opening direction.

According to a second aspect of the present invention, there is provided an applicator for applying a threaded cap to a threaded neck of a container to achieve substantial thread engagement,
15 the applicator comprising: holding means for holding at least one of the cap and the container; application means for applying the cap to the neck such that the threads of the cap and the neck are substantially fully engaged; and means for rotating the cap relative
20 to the neck in an opening direction whilst supporting the cap with respect to the neck, such that the threads of the neck and the cap are in alignment prior to application of the cap to the neck.

Advantageously, the application means may
25 comprise means for applying an axial force to at least one of the cap and the neck in the direction of the other of the cap and the neck such that the threads on the cap and the threads on the neck move past each other and interengage. Alternatively, the application
30 means may comprise means to rotate the cap relative to the neck in a closing direction. Preferably, the application means comprises rotational drive means.

Advantageously, the means for rotating the cap relative to the neck in an opening direction may
35 comprise a second rotational drive means different from said rotational drive means to drivingly rotate the cap relative to the neck in a closing direction,

the applicator further comprising means to selectively activate one of the two rotational drive means.

Alternatively, the rotational drive means may be coupled to the holding means via a gear box, the rotational drive means being adapted to selectively rotate the holding means in one of both an opening direction and a closing direction.

In a further alternative, the rotational drive means may be coupled to the holding means by clutch means, the holding means being adapted to be rotated against the clutch means in a direction opposite to the direction of rotation of the rotational drive means. Preferably, engagement means are provided to engage the holding means and rotate the holding means in an opening direction against the direction of rotation of the rotational drive means.

Advantageously, the engagement means comprises a first formation which positively engages with a second formation provided on the holding means, relative movement between the first and second formations causing the cap to rotate with respect to the neck in an opening direction. Alternatively, the engagement means comprises a first surface which frictionally engages a second surface provided on the holding means, relative movement between the first and second surfaces causing the cap to rotate with respect to the neck in an opening direction.

Advantageously, the duration of engagement between the engagement means and the holding means causes the cap to rotate with respect to the neck through an angle of at least 360° .

Preferably, the duration of engagement between the engagement means and the holding means causes the cap to rotate with respect to the neck through an angle of between 36° and 720° .

Advantageously, the applicator comprises a plurality of holding means, each for holding at least

one of a respective cap and container combination, the rotational drive means being common to each of the plurality of holding means. Preferably, the rotational drive means is coupled to each of the plurality of holding means via respective clutch means such that one or more of the holding means may be rotated against the respective clutch means in a direction opposite to the direction of rotation of the rotational drive means while the remainder of the plurality of holding means are rotated in the direction of the rotational drive means. Preferably, the engagement means is common to the plurality of holding means.

According to a third aspect of the present invention, there is provided a reverse drive mechanism for use with an applicator for applying a threaded cap to a threaded neck of a container to achieve substantial thread engagement, the applicator comprising holding means for holding at least one of the cap and the container; rotational drive means to rotate the cap relative to the neck in a closing direction such that the threads of the cap and the neck are substantially fully engaged; and clutch means interposed between the rotational drive means and the holding means such that the holding means is adapted to be rotated against the clutch means in a direction opposite to the direction of rotation of the rotational drive means, the reverse drive mechanism comprising engagement means to engage the holding means and rotate the holding means in an opening direction against the direction of rotation of the rotational drive means whilst supporting the cap with respect to the neck such that the threads on the neck and the cap are in alignment prior to the rotational drive means rotating the cap relative to the neck in a closing direction.

Advantageously, the engagement means comprises a

first formation which positively engages with a second formation provided on the holding means, relative movement between the first and second formations causing the cap to rotate with respect to the neck in an opening direction.

Alternatively, the engagement means may comprise a first surface which fictionally engages a second surface provided on the holding means, relative movement between the first and second surfaces causing the cap to rotate with respect to the neck in an opening direction.

Advantageously, the duration of engagement between the engagement means and the holding means causes the cap to rotate with respect to the neck through an angle of at least 360° .

Preferably, the duration of engagement between the engagement means and the holding means causes the cap to rotate with respect to the neck through an angle of between 36° and 720° .

BRIEF DESCRIPTION OF THE DRAWINGS

An embodiment of the present invention will now be described by way of example with references to the accompanying drawings in which:

Figure 1 shows a schematic plan view of a filling station embodying the present invention,

Figure 2 shows a side view of a capping station of the filling station of Figure 1,

Figure 3 shows a side view of a capping head used in the capping station of Figure 2, and

Figure 4 shows a side elevation of a capping station embodying the present invention.

DETAILED DESCRIPTION OF THE DRAWINGS

Referring to figure 1, there is shown an example of a filling station 2 in which containers, not shown, are filled, for example, with a liquid. The containers are then closed with a cap before moving on to be further processed if required. The neck of the container and the cap have complementary threads for resealable engagement of the container by the cap. It will be understood that either the cap will be internally threaded and the neck externally threaded or else the cap externally threaded and neck internally threaded.

As can be seen in figure 1, the containers enter the filling station at the container in-feed 2 and are transported onto a first transfer wheel 4. In the example shown, this transfer wheel rotates about an axis in an anticlockwise direction. The first transfer wheel 4 is located adjacent the filler 6 which is rotating about an axis in the opposite direction to the first transfer wheel 4. The filler 6 has a radius greater than that of the first transfer wheel 4.

Once the containers are transferred to the filler 6 they are transported around the circumference of the filler and are filled with the desired material, for example a potable liquid. Once the containers have been filled they continue around the circumference of filler 6 until they reach a second transfer wheel 8.

The second transfer wheel 8 rotates about an axis in a direction opposite to that of the filler 6, shown as anti-clockwise. When the containers are transferred to the second transfer wheel 8 they move around the circumference of the second transfer wheel 8 and pass beneath a cap placement point 10. The cap placement point 10 is not shown in detail, but it is here that a cap is placed or otherwise rested on the neck of the container such that the threads of the cap and neck of the container are not significantly

engaged. This placement may be by means of either the "pick and place" method or "pick-off" method previously described. At a point on the circumference of the second transfer wheel 8, after the containers have passed under the cap placement point 10, the containers are transferred to a capping station 12. Capping station 12 rotates about an axis in a direction opposite to that of the second transfer wheel 8, shown as clockwise.

10 The capping station 12 has a number of capping heads 14 which rotate about the axis of the capping station 12. When the container is being transported around the axis of the capping station 12, it is brought into contact with a capping head 14 and the cap is applied to the neck of the container such that the threads of the cap and the threads of the container become substantially fully engaged.

15 At a point on the circumference of the capping station 12, and after the cap has been applied to the container neck, the container is passed to a third transfer wheel 16. The third transfer wheel 16 rotates about an axis in a direction opposite to that of the capping station, shown as anticlockwise. The containers, which are now filled and sealed, are removed from the filling station 1 by the third transfer wheel 16 along out-feed 18 prior to any necessary further processing.

20 Figure 2 shows a side view of a capping station 12 such as that used in the filling station of figure 1. A container 20 has a neck 22 on which has been placed a cap 24. The container 20 is supported on a stand 26. The stand 26 is capable of translational motion by virtue of a rolling support member 28, the stand being located on a platform 30. The container 20 is held within two pairs of retaining rails 32 (only one of which is shown) located on opposite sides of the container 20. Located directly above container

20 is a capping head 14, which will be discussed in greater detail below. The capping head 14 is attached via shaft 34 to capping station 12.

5 The arrow on Figure 2 shows the direction of motion of the container 20 as it moves in the capping station 12. The stand 26 and container 20 move at substantially the same speed as the capping head 14, so that the container 20 and capping head 14 remain in direct axial alignment. As the container moves along
10 the platform 30 it is elevated at step 36, so that the cap 24 is received within the capping head 14. At this point it is possible for the final application of the cap 24 to the neck 22 to take place, so that the threads of the cap and the neck come into
15 substantially full engagement.

 Figure 3 shows a detailed side view of a capping head 14, such as that used in figure 2. The capping head comprises a chuck 38, in which is provided a cap recess 40. The cap recess 40 is sized such that a cap
20 24 received within the cap recess can be gripped sufficiently so that any torque applied to the capping head 14 will be directly applied to the cap 24. This transfer of torque from the capping head 14 to the cap 24 may be achieved by means of a frictional material
25 within the cap recess 40, or by any other method, for example the positive engagement of a formation provided on the capping head with a corresponding formation provided on the cap.

 The chuck 38 is coupled to shaft 34 via a head
30 load spring 42. The head load spring 42 provides a resilience to the capping head 14 on the axial direction. Above the head load spring 42, the shaft 34 is attached to a clutch mechanism 44, which may take any of the following forms, electrical, magnetic
35 or mechanical. The capping head 14 is then attached to a motor, not shown, which provides rotational drive to the capping head 14, to rotate the cap 24 with

respect to the container 20 until a predefined torque is achieved between the cap 24 and the neck 22.

As has been previously discussed, a problem has been identified in that the threads of the cap and neck can become cross-threaded during the initial placement of the cap on to the neck. A method of solving this problem is to initially rotate the cap in an opening direction, such that any misalignment is corrected, prior to subsequently applying the cap to the container neck.

In one embodiment of the present invention there is provided a capping head 14 which is coupled to both a first and a second motor. These motors provide rotational drive in both a clockwise and anticlockwise direction. One of these directions will rotate the cap 24 relative to the neck 22 in an opening direction and the other will rotate the cap 24 relative to the neck 22 in a closing direction. Means are provided on the capping station 12 to selectively couple the capping head 14 first to that motor which rotates the cap in the opening direction and then to that motor which rotates the cap in the closing direction. The ability of the capping station 12 to provide both an opening and closing rotation to the cap 24 will prevent any cross-threaded caps from being applied to the container neck and so remove one cause of subsequent leakage.

The capping head 14 in this particular embodiment rotates in an opening direction after the cap has been placed on the neck 22 of the container and after the cap has been received in the cap recess 40 of the capping head 14. This opening rotation should be through an angle sufficient to uncross the threads. For example in a cap having four starts the rotation is preferably through an angle of at least 90°. However, it will be understood that the opening rotation may be through any number of turns sufficient

to remove cross-threading and may, for example, be through an angle within the range from 36° and 720° . Subsequent to the rotation in the opening direction the second rotational drive rotates the capping head 14, and therefore the cap 24, in a closing direction, until a predetermined torque is achieved between the cap and the neck of the container.

In a second embodiment of the present invention the capping head 14 is coupled to only one motor but that motor is in turn coupled to a gear box and the capping head is coupled to the output of the gear box. The gear box enables the rotational drive from the motor to be provided to the capping head 14 in either an opening or a closing direction. Again, means are provided to selectively actuate the gear box so that the capping head is initially rotated in an opening direction before subsequently being rotated in a closing direction. This results in a method of addressing the risk of cross-threading similar to that described with respect to the first embodiment, but without the need for a second rotational drive motor.

In a further embodiment of the invention a single motor is provided to rotate the capping head 14 in a direction that will rotate the cap in a closing direction with respect to the container neck. However, the motor is coupled to the capping head 14 by means of a clutch. The provision of a clutch enables the capping head to be forceably rotated in a direction opposite to the direction of rotation of the motor without damaging the motor or any of its constituent parts.

Figure 4 shows part of a capping station in accordance with this further embodiment. The capping station 12 comprises eight capping heads 14 rotating in a circle indicated by arrows 46 about an axis of the capping station. In addition, each capping head 14 is rotating about its own axis, indicated by arrows

48, under the action of a common motor (not shown). However, each capping head 14 is coupled to that common motor by means of a respective clutch, also not shown. Each of the capping heads 14 is provided with
5 a shoulder 50 which may be formed on the chuck 38 or else as an annular protrusion on the shaft 34. A plate 52 is provided to one side of the capping station 12 and as the capping heads 14 rotate about the axis of the capping station as indicated by arrows
10 46 so each of the shoulders in turn engage a surface of plate 52. As the capping heads 14 continue to rotate about the axis of the capping station 12 so the shoulder 50 slides along the plate 52. At the same time, the frictional engagement between the shoulder
15 50 and the plate 52 causes the capping head in engagement with the plate to rotate against its clutch in a direction opposite to that in which it is being driven by the motor. This in turn results in the cap received within the chuck 38 being rotated in an
20 opening direction with respect to the container neck. However, as soon as the capping head 14 moves out of engagement with the plate 52, the frictional engagement responsible for the reverse rotation is removed thereby enabling the motor to resume rotation
25 of the chuck 38 in a direction that will be rotate the cap in a closing direction with respect to the container neck. This particularly elegant means of providing a reverse drive can be retrofitted to existing capping machines to alleviate the problems
30 associated with cross-threading between caps and container necks. The plate 52 is preferably of a length to ensure a reverse rotation of at least 360° although it will be understood that, depending on the number of starts and the length of the threads
35 involved, a reverse rotation of between 36° and 720° may be sufficient to alleviate the problem. Preferably the plate 52 is biased in the direction of

arrows 54 to ensure the necessary frictional engagement with shoulder 50.

Although in this last embodiment the reverse rotation of the capping head 14 has been described as
5 by means of the frictional engagement of the plate 52 with the shoulders 50, it will be understood that means may be provided to positively engage each of the capping heads in turn and so rotate the capping head
10 against the clutch in a direction opposite to the direction of rotation of the motor. For example, the plate 52 may be replaced by a rack having teeth which might engage with corresponding teeth provided on the capping heads 14.

15

CLAIMS:

1. A method of applying a threaded cap to a threaded neck of a container, the method comprising the steps of:

5 placing the cap on the neck of the container;
 rotating the cap relative to the neck in an opening direction whilst supporting the cap with respect to the neck; and

10 applying the cap to the neck so as to achieve substantial thread engagement.

2. A method as claimed in claim 1, wherein the cap is rotated relative to the neck in an opening
15 direction through an angle of at least 360°.

3. A method as claimed in claim 1, wherein the cap is rotated relative to the neck in an opening
20 direction through an angle of between 36° and 720°.

4. A method as claimed in any preceding claim, wherein the cap is applied to the neck by means of an axial force which causes the threads on the cap and the threads on the neck to move past each other and
25 then interengage.

5. A method as claimed in any of claims 1 to 3, wherein the cap is applied to the neck by rotation of the cap relative to the neck in a closing direction.

6. A method as claimed in claim 5, wherein the cap is drivingly rotated with respect to the neck by rotational drive means in both the opening and closing directions.

7. A method as claimed in claim 5, wherein the cap is drivingly rotated by rotational drive means in the

closing direction and is rotated against the rotational drive means in the opening direction.

5 8. An applicator for applying a threaded cap to a threaded neck of a container to achieve substantial thread engagement, the applicator comprising:

holding means for holding at least one of the cap and the container;

10 application means for applying the cap to the neck such that the threads of the cap and the neck are substantially fully engaged; and

15 means for rotating the cap relative to the neck in an opening direction whilst supporting the cap with respect to the neck, such that the threads of the neck and the cap are in alignment prior to application of the cap to the neck.

9. An applicator as claimed in claim 8, wherein the application means comprises means for applying an axial force to at least one of the cap and the neck in the direction of the other of the cap and the neck such that the threads on the cap and the threads on the neck move past each other and interengage.

25 10. An applicator as claimed in claim 8, wherein said application means comprises means to rotate the cap relative to the neck in a closing direction.

30 11. An applicator as claimed in claim 10, wherein said application means comprises rotational drive means.

35 12. An applicator as claimed in claim 11, wherein said means for rotating the cap relative to the neck in an opening direction comprises a second rotational drive means different from said rotational drive means to drivingly rotate the cap relative to the neck in a

closing direction, the applicator further comprising means to selectively activate one of said two rotational drive means.

5 13. An applicator as claimed in claim 11, wherein said rotational drive means is coupled to said holding means via a gear box, said rotational drive means being adapted to selectively rotate said holding means in one of both an opening direction and a closing
10 direction.

14. An applicator as claimed in claim 11, wherein said rotational drive means is coupled to said holding means via clutch means, said holding means being
15 adapted to be rotated against said clutch means in a direction opposite to the direction of rotation of said rotational drive means.

15. An applicator as claimed in claim 14, wherein
20 engagement means are provided to engage said holding means and rotate said holding means in an opening direction against the direction of rotation of said rotational drive means.

25 16. An applicator as claimed in claim 15, wherein said engagement means comprises a first formation which positively engages with a second formation provided on said holding means, relative movement between said first and second formations causing said
30 cap to rotate with respect to the neck in an opening direction.

17. An applicator as claimed in claim 15, wherein
35 said engagement means comprises a first surface which frictionally engages a second surface provided on said holding means, relative movement between said first and second surfaces causing said cap to rotate with

respect to the neck in an opening direction.

18. An applicator as claimed in any of claims 15 to 17, wherein the duration of engagement between said engagement means and said holding means causes said cap to rotate with respect to the neck through an angle of at least 360°.

19. An applicator as claimed in any of claims 15 to 17, wherein the duration of engagement between said engagement means and said holding means causes said cap to rotate with respect to the neck through an angle of between 36° and 720°.

20. An applicator as claimed in any of claims 11 to 19 comprising a plurality of holding means, each for holding at least one of a respective cap and container combination, said rotational drive means being common to each of said plurality of holding means.

21. An applicator as claimed in claim 20, wherein said rotational drive means is coupled to each of said plurality of holding means via respective clutch means such that one or more of said holding means may be rotated against said respective clutch means in a direction opposite to the direction of rotation of said rotational drive means while the remainder of the plurality of holding means are rotated in the direction of said rotational drive means.

22. An applicator as claimed in claim 21, wherein said engagement means is common to said plurality of holding means.

23. A reverse drive mechanism for use with an applicator for applying a threaded cap to a threaded neck of a container to achieve substantial thread

engagement, the applicator comprising:

holding means for holding at least one of the cap and the container;

5 rotational drive means to rotate the cap relative to the neck in a closing direction such that the threads of the cap and the neck are substantially fully engaged; and

10 clutch means interposed between said rotational drive means and said holding means such that the holding means is adapted to be rotated against said clutch means in a direction opposite to the direction of rotation of said rotational drive means, the reverse drive mechanism comprising engagement means to engage said holding means and rotate said holding
15 means in an opening direction against the direction of rotation of said rotational drive means whilst supporting the cap with respect to the neck such that the threads on the neck and the cap are in alignment prior to said rotational drive means rotating the cap
20 relative to the neck in a closing direction.

24. A reverse drive mechanism as claimed in claim 23, wherein said engagement means comprises a first formation which positively engages with a second
25 formation provided on said holding means, relative movement between said first and second formations causing said cap to rotate with respect to the neck in an opening direction.

30 25. A reverse drive mechanism as claimed in claim 23, wherein said engagement means comprises a first surface which frictionally engages a second surface provided on said holding means, relative movement between said first and second surfaces causing said
35 cap to rotate with respect to the neck in an opening direction.

26. A reverse drive mechanism as claimed in any of
claims 23 to 25, wherein the duration of engagement
between said engagement means and said holding means
causes said cap to rotate with respect to the neck
5 through an angle of at least 360°.

27. A reverse drive mechanism as claimed in any of
claims 23 to 25, wherein the duration of engagement
between said engagement means and said holding means
10 causes said cap to rotate with respect to the neck
through an angle of between 36° and 720°.


28. A method of applying a threaded cap to a threaded
neck of a container, the method being substantially as
15 herein described with reference to the accompanying
drawings.

29. An applicator for applying a threaded cap to a
threaded neck of a container, the applicator being
20 substantially as herein described with reference to
the accompanying drawings.

30. A reverse drive mechanism for use with an
applicator for applying a threaded cap to a threaded
25 neck of a container, the reverse drive mechanism being
substantially as herein described with reference to
the accompanying drawings.

1/4

Fig 1



THIS PAGE BLANK (USPTO)




FIG 2

THIS PAGE BLANK (USPTO)

3/4




FIG 3

THIS PAGE BLANK (USPTO)




FIG 4

THIS PAGE BLANK (USPTO)